

Acom 1000 HF Linear Amplifier New LAMCO Barnsley

ACOM 1000 160-6m



Price: £2,259.95

SKU: Acom 1000 New LAMCO Barnsley

In stock: 1

Product Categories: [LAMMY'S SPECIAL PROMOTIONS](#), [ACOM](#), [AMPLIFIERS](#), [COMMERCIAL LINEAR AMPLIFIERS](#)

Product Tags: [Acom 1000 HF Linear Amplifier](#)

Product Page: <https://www.hamradio-shop.co.uk/product/acom-1000/>

Product Summary

£2259.95

Product Description Acom 1000 HF Linear Amplifier

Acom 1000 HF Linear Amplifier



ACOM 1000 HF Linear Amplifier is the world's best value in an amateur HF amplifier. The ACOM 1000 gives you a comfortable 1000 watts output on all amateur bands from 160 through 6 meters. **FEATURES**
Acom 1000 Easy to operate
The plate-load True Resistance Indicator (TRI) is a powerful tuning aid which, together with the automatically controlled input attenuator, helps the operator to quickly and precisely match antennas (5-10 seconds typically). The auto-operate function (when enabled) maintains the amplifier in OPERATE mode for you, thus saving manual operations and time. **No antenna tuners**

Acom 1000

The amplifier will perform the functions of an antenna tuner for VSWR up to 3:1, thus enabling you change antennas faster and use them over a wider frequency range (saving tuning time).

User-friendly

Acom 1000

An amplifier that is both user-friendly, and that looks after itself. It is designed to safely withstand up to 500W reflected power, up to 100 milliseconds duration of drive spikes, drive RF "tails" after a PTT or KEY release, operator's inadvertent tuning errors etc. It would also not cease to function with a "soft" AC line and would deliver more than half power at only 75% of nominal mains voltage. Withstands up to 10 milliseconds (down to zero) voltage drops, and up to +15% line voltage spikes - important particularly when used at field days, Dxpeditions, etc.

LCD comment display

Acom 1000

Text messages, 12 parameters, and strip peak-reading PEP meter displayed on a dot-matrix, back-lighted LCD. LED indicators are provided for OPERATE, attenuator-on, and ON/OFF conditions.

Easy maintenance

Acom 1000

Signatures of the amplifier internal status are stored in a nonvolatile memory for 7 most recent auto protection trips. This information is used for diagnostics.

Virtually silent QSK

Acom 1000

The input bypassing and the vacuum antenna relays are very quiet even in CW mode due to their special mounting.

Broadband input matching

Acom 1000

Resulting in very good load to the transceiver over the entire spectrum 1.8-54MHz.

Single 4CX800A (GU74B)

Acom 1000

A Svetlana high performance ceramic-metal tetrode with plate dissipation of 800W is employed (forced air cooling, grid-driven).

Tube protection

Acom 1000

Permanent monitoring and protection of plate and grid voltages and currents, as well as of the exhaust temperature.

Frequency Coverage: All amateur bands 1.8-54MHz; extensions and/or changes on request.

- Power Output: 1000W PEP or continuous carrier, no mode limit.
- Intermodulation Distortion: Better than 35dB below rated output.
- Hum and noise: Better than 40dB below rated output.
- Harmonic Output Suppression:
 - 1.8-29.7MHz - better than 50dB below rated output;
 - 50-54MHz - better than 66dB below rated output.
- Input and Output Impedances:
 - nominal value: 50 Ohm unbalanced, UHF (SO239) type connectors;
 - input circuit: broadband, VSWR less than 1.3:1, 1.8-54MHz continuously (no tunings, no switching);
 - bypass path VSWR less than 1.1:1, 1.8-54MHz continuously;
 - output matching capability: better than VSWR 3:1 or greater at reduced output levels.

- RF Gain: 12.5dB typically, frequency response less than 1dB (50 to 60W drive power for rated output).

Acom 1000

Primary Power: 170-264V (200, 210, 220, 230 & 240V nominal taps, 100, 110 & 120V taps on request, +10%-15%tol.), 50-60Hz, single phase, 2000VA consumption at rated output.

- Complies with CE safety and EMC requirements, as well as FCC-regulations (6,10 & 12m bands lock provided).

- Size & Weight (operating):

-WxDxH: 422x355x182mm, 22kg.

-(16.6x14x7.2 inches, 48.5lbs)

- Operating environments:

- temperature range: 0...+50 degs.Celsius;

- humidity: up to 75% @ +35 degs.Celsius.

- height: up to 3000m above sea level without output deterioration

Acom 1000

Product Gallery



ACOM 1000 160-6m

